

Technical datasheet No: 09-LED-P-SL-05-2013

LED Hall-Spotlight

Art. Nr. : SWS-HB-515.200; SWS-HBD-515.200; SWS-HB-515.400



Specification

Item	SWS-HB-515.200	SWS-HBD-515.200	SWS-HB-515.400
Product	LED Hall spotlight	LED Hall spotlight	LED Hall spotlight
Power	200 W	200 W	400 W
Number of LEDs / Brand	1 pc / Bridgelux	1 pc / Bridgelux	1 pc / Bridgelux
CRI	≥ 75 RA	≥ 75 RA	≥ 75 RA
Lifetime	> 50,000 hours	> 50,000 hours	> 50,000 hours
Colour temperature	2.700 K-6.500 K	2.700 K-6.500 K	2.700 K-6.500 K
Luminous flux	16.200 lm	16.200 lm	29.200 lm
Dimensions WxH	230 x 250 mm	230 x 250 mm	328 x 280 mm
Cover	clear	clear	clear
Driver	Meanwell	Meanwell/dimmable	Meanwell/dimmable
Beam angle	110° or 40°	110° or 40°	110° or 40°
Net weight	12,5 kg	12,5 kg	12,5 kg
Input voltage	85~265 V	85~265 V	85~265 V
Certificates	CE, RoHS	CE, RoHS	CE, RoHS